



## Magnetic Agricultural Waste as an Adsorbent for Improved Bioremediation and Clarification of Textile Effluents

Rajalakshmi V<sup>1</sup>, Geethadevi C<sup>2</sup>, S. Karthik Sundaram<sup>3</sup>, Rajendran R<sup>4</sup>, Abirami M<sup>5\*</sup>

<sup>1,5\*</sup>PG and Research Department of Microbiology, Dwaraka Doss Goverdhan Doss Vaishnav College, Chennai, TamilNadu, India.

<sup>2,4</sup>PG and Research Department of Microbiology, PSG College of Arts and Science, Coimbatore, Tamilnadu, India

<sup>3</sup>Department of Microbiology, Dr NGP College of Arts and Science, Coimbatore, Tamilnadu, India

(Received: 23 November 2023      Revised: 22 December      Accepted: 29 December)

### KEYWORDS

Effluent, consortium, immobilization, absorbent, nanoparticles, decolourisation.

### ABSTRACT:

Textile dyeing industry is considered as one of the largest generators of waste water in India. Dyes released by the textile industries cause a major threat to environmental safety. Apart from physical and chemical method, dye decolourisation through biological means can apply to the dye with wide range. The present study focused on the screening of microbial isolates from the effluent with respect to the synthetic dye decolourisation. Three bacterial and two laccase producing fungal species were isolated, that are efficient in decolourising the synthetic dyes. These isolates were identified as *Bacillus* sp., *Pseudomonas* sp., *Acinetobacter* sp., *Aspergillus niger* and *Aspergillus fumigatus*. Effluent was treated using the individual microbes, microbial consortium and immobilized form of microbial consortium. Both the treatment showed better efficiency when compared to individual microbes, but the sludge settlement was again a threat. Effluent treated by the immobilized microbial consortium with peanut husk and iron oxide nanoparticles showed the highest decolourisation rate as well as sludge was removed during the treatment. By using the magnetically induced biological waste the removal of dyes and separation of sludge contents can be achieved with low cost. This kind of absorbent could be potentially used for the treatment of textile dye effluent.

### 1. Introduction

Textile industrial effluent associated with water pollution is a matter of great concern over decades. In textile industries, numerous number of chemicals are used for dying variety of fabric materials. On

commercial basis, among different dyes, azo dyes are used in most of the dyeing units in Tiruppur district due to their colour intensity and cheap cost. These azo dyes have poor exhaustion properties that end up as the effluent of the dyeing industries (Puvaneshwari *et al.*, 2006). Azo dyes are



considered to be biorecalcitrant under aerobic conditions that are cleaved under oxygen limiting conditions leading to the formation of toxic aromatic amines. These aromatic amines could not be further reduced under limited oxygen but are auto-oxidizable or could be mineralized by microbes at a faster rate under aerobic condition. But, this treatment procedure is time consuming and is not feasible commercially, also the cost of treating the effluent under anaerobic situation is commercially demanding. The disposal of synthetic dyes into the environment causes serious damage as they intensely affect the photosynthetic activity of hydrophytes by limiting the light penetration and their breakdown products may be toxic to some aquatic organisms (Senan and Abraham, 2004). It also affects water bodies, ecosystem integrity, soil fertility and plant growth. The azo dyes are becoming a great concern due to their visible colour, biorecalcitrance and toxicity to animals and humans (Darwesh *et al.*, 2008).

Sludge, a residue from textile wastewater treatment, contains toxic and hazardous materials remaining from textile processing and after textile wastewater treatment. Thus, colored effluent and sludge problems are serious for textile industry management and a development of appropriate treatment system is desired. Remotion is a new technique that enables the utilization of the biological and chemical technologies (Sathyabama *et al.*, 2013). Biological approach involves the microbial degradation mediated by enzyme. Many research study reported that the enzymatic approach had attracted much interest with regard to decolourisation and degradation of azo dyes in wastewater (Kirby *et al.*, 2000). Among different enzymes, laccase have been extensively studied for their degradation of azo dyes

(Novotny *et al.*, 2004). These enzymes are multicopper phenol oxidases that decolourise azo dyes through a highly nonspecific free radical mechanism forming phenolic compounds, thereby avoiding the formation of toxic aromatic amines (Peralta-Zamora *et al.*, 2003).

The present work was focused on the bioremediation not only of a specific group of xenobiotic textile dyes, but also various classes of dyes. Remotion technique was carried using immobilized microbial consortium, peanut husk as absorbent and iron oxide nanoparticles in effectively eliminating the dyes from escaping to the environment. This enables a clear separation of the sludge developed during the effluent treatment. By subjecting the magnetically induced adsorbent to a magnetic field, the sludge component would be separated out more effectively enhancing the efficiency of the treatment process by manifolds. The production rate of textile sludge-based adsorbent depends on the generation rate of sludge from the textile wastewater treatment processes.

## 2. Materials and Methods

### Dyes and Chemicals

Dyes used in the study (Indigo blue, Remazol brilliant violet 5R, Reactive Black 5, Reactive red 120 and Reactive Orange 16) were obtained from Sigma Aldrich a part of Merck. Peanut husk was procured from Shree Krishna stores, Coimbatore. Hi-Media chemicals and media were used for the work.

### Collection of effluent sample

Sample collected from Textile dyeing industry outlet, Tirupur District, Tamilnadu, India. The samples were collected in polyethylene cans previously washed with 6M HNO<sub>3</sub> and distilled water. The collected sample was shifted to the



laboratory as soon as possible for the analysis of various physico - chemical parameters. Some parameters like temperature, pH and colour were recorded at the sampling spot itself by adopted the method recommended by APHA (1995). The collected samples were stored at 4°C for further analysis.

#### **Characterization of the effluent using physico-chemical parameters**

The raw effluent was characterized by analyzing the following physico-chemical parameters which includes Colour, Turbidity, Chemical Oxygen Demand (COD), Total Solids (TS), Total Suspended Solids (TSS), Total Dissolved Solids (TDS), pH, and Hardness were chosen in accordance with the regulations of Tamilnadu Pollution Control Board (TNPCB).

#### **Preliminary screening and isolation of dye decolourising microbial strain**

The screening of bacterial and fungal isolates from textile effluent was based on synthetic dye decolourisation ability using plate assay method. About five different synthetic dyes (Indigo blue, Remazol brilliant violet 5R, Reactive Black 5, Reactive red 120, Reactive Orange 16) were 0.01% amended in solid media individually. Microbial strain isolations were carried out by serially diluting textile effluent sample was subsequently plated onto the solid media containing dye plates. The plates were incubated at 37°C (24 hour) for bacteria and 48 hours at 28°C for fungi (Anamika and Sarabjeet, 2013). After incubation, those bacteria and fungi which are capable of decolourising the dyes were formed the zone of clearance around their colonies. The morphologically distinct microbial isolates showing clear zone around their colonies due to decolourisation of dye were selected for further studies. The

pure cultures were stored at 4°C for further analysis.

#### **Secondary screening of selected bacterial isolates**

The selected bacterial strains were subjected to secondary screening using decolourisation assay. The bacterial strains were inoculated into the nutrient broth containing 0.01% of five different dyes individually. After incubation, the samples (5 ml) were centrifuged at 10,000 rpm for 15 minutes and its absorbance was measured at  $\lambda_{\max}$  of the particular dye. The dye free uninoculated medium was used as blank (control). All assays were performed in triplicate and compared with control. The decolourisation efficiency of bacterial isolates was expressed in terms of percentage by using the following equation (Khelifi *et al.*, 2009).

$$\text{Decolourisation (\%)} = 100 \times \frac{(D_i - D_t)}{D_i} \dots\dots\dots (1)$$

Where,  $D_i$  = initial absorbance;  $D_t$  = final absorbance of decolourised medium after specified time. The Absorbance maxima ( $\lambda_{\max}$ ) for each dye were obtained over visible range (nm) using UV-Vis Spectrophotometer (Elico SL 244) (table 1).

#### **Screening of laccase producing fungal isolates**

The selected dye degrading fungal isolates were inoculated in the plate containing 15ml of 4% potato dextrose agar amended with 0.01% of Guaiacol. The plates were incubated at 30°C for 1 – 3 days. The presence of brick red colour around the mycelium was considered as guaiacol oxidizing extracellular laccase secreting organism (Kiiskinen *et al.*, 2004).

#### **Identification of selected microbial isolates**

The bacterial isolates were identified using standard biochemical and microscopic (Gram's staining) techniques.



The selected efficient laccase producing fungal strains were subjected to microscopic identification using Lactophenol cotton blue technique (Cappuccino and Sherman, 1996).

### **Compatibility analysis of selected microorganisms**

To prepare the microbial consortium, the microbial cultures must be compatible with each other. The selected dye degrading organisms were swabbed on the Luria Bertani (LB) agar plates individually in each plate. After inoculation, wells were cut by using gel puncture. In each of these wells about 10 $\mu$ l of the culture supernatant were added expect the culture of organisms swabbed in the plate (Rajendran *et al.*, 2011). The plates was incubated for 48 hours at room temperature and observed for the formation of zone of clearance around the wells. The presence and absence of zone around the well indicates the compatible and incompatible of the organism respectively. The microbial cultures when compatible with decolourisation capabilities were chosen to construct the microbial consortia.

### **Synthesize of iron oxide nanoparticles**

Magnetically responsive nanocomposite materials were prepared by modification of diamagnetic materials with magnetic fluids. The iron oxide nanoparticles were synthesized using the co-precipitation method. The ferric chloride (FeCl<sub>3</sub>) solution (3.7g/500ml distilled water) and ferrous sulphate (FeSO<sub>4</sub>) solution (9.4g/500ml distilled water) were prepared individually (Safarik *et al.*, 2007). Both the solutions were mixed in the ratio of 1:1 and stirred at 80°C for 10 minutes. Once the iron compounds have completely dissolved, 25 % of the ammonia solution was added in drop wise to the reaction solution and continuous stirring was resumed until the complete black magnetite

precipitation was achieved (pH 9-11). After the ammonia reaction, the reaction solution forms a black precipitate in the bottom of the reaction flask (Mutasim, 2015). After the solution was cooled at room temperature, the precipitates were separated by a permanent magnet and washed several times with distilled water until pH neutralize followed by acetone wash twice. Finally, the precipitate was dried in oven at 60 - 70°C to obtain the iron oxide nanoparticles (Poedji *et al.*, 2013).

### **Characterization of the synthesized nanoparticles**

The synthesised iron oxide nanoparticles were characterized using Ultra Violet – Visible (UV - Vis) Spectrophotometer and Dynamic Light Scattering (DLS) analysis. The synthesized iron oxide nanoparticles after diluting with distilled water; the sample was monitored by measuring of the UV – Vis spectrophotometer (Elico SL 244) at the wavelength of 330 – 750 nm. The technique of DLS has been widely employed for sizing Magnetic nanoparticles in liquid phase. The average nanoparticles size of a magnetic iron oxide nanoparticles were determined by DLS and the results were recorded using Malvern zetasizer version 2.2. There were 100 scans for each sample and the mean was taken as the average particle size and zeta potential of the sample.

### **Immobilized beads for the effluent treatment**

The immobilized microbial consortia have a broad application in the field from industrial to environmental process especially in the field of waste water treatment. The remediation efficiency of free cell was enhanced by immobilizing the microbes in a matrix of sodium alginate. About 3.6 % of sodium alginate was prepared with 5% of microbial free cells.



The solution was taken in a pipette/beaker and was allowed drop by drop into the beaker containing 2% calcium chloride solution and it was collected in the form of beads (Wang *et al.*, 2003). The immobilization of the microbial consortium containing magnetically induced adsorbent with iron oxide nanoparticles were also prepared using the same procedure in addition, each 1% of magnetically induced agricultural waste (peanut husk) and the synthesized iron oxide nanoparticles were mixed with the alginate.

### **Treatment of the collected effluent sample**

The effluent sample was treated using the microbial cultures with iron oxide nanoparticles on immobilized and non-immobilized condition. About 5% of the log phase microbial consortia, immobilized microbial consortia; immobilized microbial consortia with iron oxide nanoparticles amended in absorbent husk; free cells of microbial consortia were added in the effluent individually. The samples were incubated in a metabolic shaker (120 rpm) for 15 days at room temperature. The samples were retrieved from the flasks intermittently; every 48 hour and the physico chemical parameters were analyzed and statistically interpreted.

## **3. Results and Discussion**

### **Physico chemical characterization of the collected effluent sample**

The physico chemical characterizations of the collected effluent sample were analyzed based on TNCPB. The collected effluent sample colour was found to dark black. The colour of the effluent sample typically depends upon the different industrial processes. The measurement and removal of colour is essential part as it is unfit for recycling

without proper treatment. The samples had fishy odour that may be because of the presence of decaying vegetation, inorganic and organic constituents. The physicochemical analysis results of the raw effluent sample were observed and represented in table 2. In the present study, the physico-chemical values of the collected samples were higher than the permissible limit of Tamil Nadu Pollution Control Board (TNPCB) for the collected effluent sample. It confirms that the collected effluent sample may contain heavy organic and formation of toxic aromatic amines, will leads to affect the water body when released in to the environment. In order to overcome this problem the textile effluent should treated.

### **Preliminary screening and isolation of dye decolourising microbial strain**

The dye decolourising microbial colonies were screened based on the formation of visual zone of clearance was observed on the plates containing synthetic dye after incubation. Among them 15 predominant microbial cultures (10 bacterial and 5 fungal cultures) were isolated. The decolourisation of dyes was due to the degrading ability of the bacterial and fungal cultures by the breakdown of chromophore of dyes with the enzymes production. The decolourisation of the dye by organaisms could be due to the adsorption to microbial cells or due to biodegradation (Khadijah *et al.*, 2009).

### **Secondary screening of selected bacterial isolates**

The initially screened bacterial isolates were subjected to quantitative dye decolourisation by broth assay method. The percentage of dye decolourisation was calculated and represented in table 3. The results show that all the selected bacterial strain was able to decolourise the five different dyes. Whereas the bacterial





isolates 1, 2 and 3 showed 66-95% decolourisation in the aerobic shaking condition after 24 hour and thus it was selected for further studies.

#### **Screening of laccase producing fungi**

The secondary screening of fungal isolates was based on their ability to produce laccase. Two fungal sp showed positive result for the laccase production (figure 1). It was identified by the development of dark brown zone around and below the colonies. The formation of the brown colour and the incubation period required for proper growth varies with individual organism. Laccases catalyze the oxidation of both phenolic and non phenolic compounds and thus it can decolourise a wide range of synthetic dyes in the effluent thereby avoiding the formation of toxic aromatic amines (Abedin *et al.*, 2008).

#### **Identification of selected microbial isolates**

The selected pure bacterial isolates 1, 2 and 3 were tentatively identified as *Pseudomonas* sp, *Bacillus* sp, and *Acinetobacter* sp respectively. The isolated extra cellular enzyme laccase secreting two fungal strains were tentatively identified as *A. niger* (A) and *A. fumigatus* (B).

#### **Compatibility analysis of selected microorganisms**

The efficient dye decolourising bacterial isolates (1, 2 and 3) and laccase producing fungal isolates (A & B) were tested for compatibility analysis and it was found out that there was no zone of clearance observed in any of the plates swabbed with all the selected cultures individually. It indicates that the selected bacterial and fungal isolates were compatible with each other (Figure 2). This may be due to the fact that the autochthones were isolated, that would have co-existed earlier in the same environment. These

microorganisms when used as a consortium it could be used in the decolourisation of dye as well as the degradation of complex organic compounds that are present in the effluent (Rajendran *et al.*, 2011).

#### **Characterization of the synthesized nanoparticles**

The iron oxide nanoparticles ( $\text{Fe}_3\text{O}_4$ ) synthesized by co-precipitation of ferric and ferrous chloride was validated by UV-Visible spectroscopic analysis and their scanning absorbance vs wave length ( $\lambda$ ) has been established. The characteristics peaks of iron nanoparticles were observed at 585 nm (figure 3). Dynamic light scattering was processed to determine a hydrodynamic size of synthesized nanoparticles. The particle size distribution of chemically synthesized iron oxide nanoparticles are shown in figure 4. The average sizes of iron oxide nanoparticles were found to be 153.8 nm.

#### **Treatment of the collected effluent sample**

The treatment of the collected textile effluent sample was carried out using microbial free cells, immobilized microbial consortia and the immobilized magnetically induced peanut husk with iron oxide nanoparticles.

#### **Treatment of effluent with microbial free cells**

The effluent sample treated with the free cells of microbial consortia under aerobic condition was withdrawn at an interval of every 48 hours to analyse the physico-chemical characters. The uninoculated textile effluent serves as the control (Usha *et al.*, 2010). A pattern of reduction in parameters was observed up to 15 days. The physico – chemical characters showed a continuous reduction from the first day and the maximum reduction were observed at the 11<sup>th</sup> day of incubation. The physico – chemical characters like COD -



66.04%, Hardness - 51.95%, TS - 62.70%, TSS - 60.93%, TDS - 55.02%, pH - 25.92%, Turbidity - 79.86%, colour - 65.09% was observed as the maximum reduction in the effluent treated by the free microbial cell. There was only slight change occurred in few parameters after 11<sup>th</sup> day to 15<sup>th</sup> day (figure 5). A bacterium offers a cheaper and environment friendlier alternative for colour removal in textile effluents. Microbial consortia free cell treatment in effluent showed a moderate reduction of physico-chemical characters by lower operating cost, but the main drawback behind the treatment was the formation of sludge during the treatment.

### **Treatment of effluent with immobilized microbial consortia**

The collected textile effluent was treated with microbial consortium immobilized in a matrix of sodium alginate. The percentage reduction was gradually increased from 1 to 11<sup>th</sup> day after which there was only slight increase in few characters (figure 6). The COD -73.22%, Hardness - 79.60%, TS - 83.14%, TSS - 80.6%, TDS - 85.63%, pH - 33.33%, Turbidity - 88.27%, colour - 84.51%, was recorded at the end of 15<sup>th</sup> day. Once the microbial cells were immobilized, the cell viability must be concomitantly sustained over a long period of time. Thus, immobilization is advantageous for sustaining solely growing cells. The dye and the organic molecules would be adsorbed on the surface of the immobilized cells and these adsorbed molecules acts as the energy substrate for the microbes present in the core of the matrix (Bulut *et al.*, 2007). The results indicated that sodium alginate immobilized with microbial consortium can be used as an efficient and eco-friendly adsorbent for the removal of synthetic dyes (Wang *et al.*, 2008). Even though treatment attains almost 80% of the physico-chemical

reduction, sludge settlement pose a severe problem in this criteria to be focused. In order to overcome the problem of sludge formation, an adsorbent with magnetic property could be used.

### **Treatment of effluent with immobilized microbial consortia, peanut husk and iron oxide nanoparticles**

The percentage reduction of the textile dye decolourisation was calculated and graphically represented in figure 7. The maximum percentage reduction was observed at the end of 15<sup>th</sup> day COD - 83.33%, Hardness - 95.85%, TS - 98.01%, TSS - 86.04%, TDS - 98.73%, pH - 33.33%, Turbidity - 95.10%, colour - 95.22%. The treatment process effectively degrades the effluent since both the absorbents (iron oxide nanoparticles and peanut husk) and the microbes act on the dyes. Results indicated that peanut husk showed maximum biosorption capacity in removal of synthetic dyes present in the textile effluent (Wang *et al.*, 2008). Immobilized iron oxide nanoparticles trapped with the organic matters in the effluent are removed through the external magnetic force. Therefore, the treatment was found to effective when compared with the free cells and immobilized cells because of the sludge removal. Since it is cost effective and also colour removal were almost more than 90%. The peanut husk with iron oxide nanoparticles and microbial consortium effectively replaces the physical and chemical treatment.

The major advantage of this treatment is sludge free process and there would be complete removal of colour from the effluent by breaking down the chromophore of the reactive dyes and also due to the adsorption on the cell wall of microorganisms and also adsorption by the peanut husk adsorbents. This showed that



the magnetically induced peanut husk with iron oxide nanoparticles is more efficient of treating the effluent samples.

#### 4. Conclusion

The inclusion of physical, chemical and biological techniques aids in enhancing the overall potential of the developed technique (remotion). Through remotion the presence of an adsorbent (powdered agricultural waste particles peanut husk) in the immobilized bead adsorbs the dissolved dye component while the microbial system present at the core produces enzymes that would reduce the dye. From the result it was observed that peanut husk is a promising adsorbent for the removal of different types of xenobiotics dyes. Also, the sodium alginate immobilized with microbial consortium considered to be an efficient

and eco-friendly adsorbent for the removal of synthetic dyes.

Magnetic nanoparticles precipitated on the peanut husk surface both in the form of individual particles and agglomerates of particles. Magnetic modification of this material enables to use magnetic separation techniques for its rapid separation from complex samples containing different impurities, including suspended solids. The maximum adsorption capacities of tested dyes on this magnetically labeled material are relatively high. This kind of treatment has been effective in bioremediation of dumped dye stuffs and dye waste in the effluents with a lower operating cost than other remediation process. It's a key for textile industry to overcome the negative impact on the environment especially in case of coloured wastewater and sludge.

**Table 1: Maximum wavelength scan for different dyes**

Dyes	Type of dye	Maximum wavelength (nm)
Indigo blue	Reactive dye	602
Remazol brilliant violet 5R	Reactive dye	583
Reactive Black 5	Reactive dye	597
Reactive red 120	Reactive dye	538
Reactive Orange 16	Reactive dye	494

**Table 2: Physico – chemical characterization of untreated effluent sample**

Physico-chemical parameters	Observed values	TNPCB Permissible limits
COD (mg/L)	960	400
Hardness (mg/L)	820	600
TS (mg/L)	3970	2500
TSS (mg/L)	480	50
TDS (mg/L)	2050	1500
pH	10.8	6.5-9.0
Turbidity	1.5943	Not objectionable
Colour	1.9705	25HU



**Table 3: Percentage reduction of dye decolourisation by bacterial strains**

S. No	Isolated bacterial strain	% Decolourisation of synthetic textile dye				
		Indigo blue	Remazol Brilliant Violet 5R	Reactive Black 5	Reactive Red 120	Alizarine Red 5R
1	1	69.7	91.5	88.6	83.4	71.7
2	2	94.5	76.7	66.2	68.5	67.0
3	3	89.7	93.6	70.8	70.9	89.2



**Figure 1: Screening of fungal isolates for laccase production****Figure 2: Compatibility analysis for the dye decolourising microbial strains**



Figure 3: UV- VIS spectral characteristics of iron oxide nanoparticles




Figure 4: Particle size distribution of the iron oxide nanoparticles






Figure 5: Physico - chemical analysis of treated effluent sample with microbial consortia



**Figure 6: Physico - chemical analysis of treated effluent sample with immobilized microbial consortia**



**Figure 7: Physico - chemical analysis of treated effluent sample with immobilized microbial consortia amended with iron oxide nanoparticles and peanut husk**

## 5. References

1. APHA. 1995. Standard methods for the Examination of water and waste water. American Public Health Association, American Water Works Association, Water Environment federation Green berg, AE Clesceri L S, Eaton AD (eds) 18th edition 1100.
2. Cappuccino, J. G., and Sherman, N. 1996. Microbiology- a Laboratory Manual, pp. 137-49. The Benjamin/Cummings Pub. Co. Inc. New York, USA.
3. Darwesh, O. M., Wafaa, M. A., Olfat, B. S., Sedik M. Z., and Moawad, H. 2008. Degradation of synthetic aromatic textile dyes by native bacteria isolated from textile mill sites. *Int. J. Environ. Sci.*, 3: 71-80.
4. Khelifi, E., Bouallagui, H., Touhami, Y., and Hamdi, M. 2009. Enhancement of textile waste water decolorization and biodegradation by isolated bacterial and fungal strains. *Desalination and water treatment*, 2: 310-316.
5. Kiiskinen, L. L., Ratto, M., and Kruus, K. 2004. Screening for novel laccaseproducing microbes. *J. Appl. Microbiol.*, 97: 640-646.



6. Kirby, N., Marchan, R., and McMullan, G. 2000. Decolourization of synthetic textile dyes by *Phlebia tremellosa*. *FEMS Microbiology Letters*, 188: 93–96.
7. Mutasim I., Khalil. 2015. Co-precipitation in aqueous solution synthesis of magnetite nanoparticles using iron (III) salts as precursors, *Arabian journal of chemistry*, 8 (2) 2:279-284
8. Novotny, C., Svobodova, K., Kasinath, A., Erbanova, P. 2004. Biodegradation of synthetic dyes by *Irpex lacteus* under various growth conditions. *International Biodeterioration and Biodegradation*, 54:215–223.
9. Peralta-Zamora, P., Pereira, C. M., Tiburtius, E. R. L., Moraes, S. G., Rosa, M. A., Minussi, R. C., and Duran, N. 2003. Decolourization of reactive dyes by immobilized laccase. *Applied catalysis B: Environmental*, 42:131–144.
10. Poedji Loekitowati Hariani, Muhammad Faizal, Ridwan, Marsi, and Dedi setiabudidaya. 2013. Synthesis and properties of Fe<sub>3</sub>O<sub>4</sub> Nanoparticles by Co-precipitation method to removal procion dye, *International journal of environmental science and development*, 4(3): 336-340.
11. Puvaneshwari, N., Muthukrishnan, J., Gunesekaran, P. 2006. Toxicity assessment and microbial degradation of azo dyes. *Indian J Exp Biol*, 44:618-625.
12. Safarik, I., Lunackova, P., Mosiniewicz- Szablewska, E., Weyda, F., and Safarikova, M. 2007. Adsorption of water-soluble organic dyes on ferrofluid-modified sawdust. *Holzforschung*, 61:247-253.
13. Sathyabama, N., Ezhilarasu A., and Ahila, A. 2013. Microbial decolourization of the synthetic azo dyes. *Int. J. Interd. Res. Rev.*, 1(2):121-124.
14. Senan, R. C., and Abraham, E.T. 2004. Bioremediation of textile azo dyes by aerobic bacterial consortium. *Biodegra.*, 15:275-280.
15. Khadijah, O., Lee, K. K., Mohd Faiz, F., and Abdullah. 2009. Isolation, Screening and Development of Local Bacterial Consortia with Azo Dyes Decolorizing Capability. *Malaysian Journal of Microbiology*, 5: 25-32.
16. Wang, B.E., Hu, Y. Y., Xie, L., Peng, K. 2008. Biosorption behaviour of azo dye by inactive CMC immobilized *A.fumigatus* beads. *Bior esour Technol*, 99: 794-800.
17. Anamika Pokharia, and Sarabjeet Singh Ahluwalia. 2013. Isolation and screening of dye decolourizing bacterial isolates form contaminates sites. *Textile and Light Industrial Science and Technology*, 2(2):54-61.
18. Bulut, Y., Goubenli, N., and Aydin, H. 2007. Equilibrium and kinetics studies for adsorption of direct blue 71 form aqueous solution by wheat shells. *Journal of Hazadrous material*, 144: 249-261.
19. Rajendran, R., Sundaram, S. K., and Maheswari, K. U. 2011. *J. Environ. Sci. Technol.*, 4: 568-578.